

Inline Compact 900

Versatile space saving curing solution for efficient roll to roll DTF production

Designed to achieve demanding volume without compromising output quality or reliability. Featuring automatic operating mode, fast curing times and low power consumption for reduced energy costs.

The Compact 900 delivers all expected DTF shaker curer features and much more in a space saving design to provide a versatile yet extremely efficient and reliable solution for your DTF production and workflow.











Machine Features

- Powered by standard domestic plug.
- · Compatible with industry leading printer brands.
- Reliably powder, cure & filter at speeds of 20 I/m per hour.
- Film feed speed detection for easy printer integration.
- Built-in filtration and extraction for safer operation.
- Replaceable medical grade filters with automatic on-screen replacement reminders for easy maintenance.
- Thoughtful humidity and temperature sensor to help manage your DTF production environment.
- Low powder warning light for uninterrupted workflow.
- Digital touch screen with feature explanations for intuitive control.
- Machine tracking interfaces for simple diagnostics.
- Heavy duty build and reliability synonymous with Adkins.

Technical Specification

Voltage: 220-240V AC (UK-13A / EU-16A)

Power Consumption: 2.1kw (average)

Circuit Breaker: 15A

Media Size: 90cm maximum

Machine Size: $131(w) \times 114(h) \times 145(d) \text{ cm}$

Net Weight: 228KG

Package Size: 133(w) x 121(h) x 147(d) cm

Package Weight: 310KG

Minimum Workable Area: 177(w) x 150(h) x 210(d) cm

Heating: 6 x Top / 5 x Bottom Elements

Heat Up Time: Approx 15mins (100 degrees)

Oil Removal: Sealed oil collection and drainage tap

Powder Collection: Powder tray accessible from either side



With decades of experience in producing high quality engineered heat transfer solutions, Adkins is a trusted brand worldwide.

+44 1332 85 84 30 adkinsmachines.com sales@adkinsmachines.com